



Ntgrate Kult

Technical data sheet

The synthetic floorcovering »Ntgrate Kult« is a flat woven synthetic quality with a wear layer produced according to the TOPGRATE® method. In the weaving process, the TOPGRATE® technology only uses, glass-fiber reinforced, PVC yarns of which **an adhesion between the core and the skin > 20 N**. The fabric, with a **warp density of 12 threads/cm** and a weft density of an average of 9 threads/cm, is **stabilized in a heat set process**. This wear layer is a **phthalate-free plastisol laminated on a glass-fiber fleece**. The TOPGRATE® is finished with a homogeneous PVC backing.. The tiles are made on request in the dimensions listed in the catalogue and supplied in boxes of 4 m².

Thickness : ca 3,3 mm

Total Weight : ca 4.500 gr/m²

Level of use : EN 15114 : Class 33 HEAVY COMMERCIAL public areas

Vetterman : ISO 10361 : 5.000 t : ≥ 4 22.000 rev : ≥ 3,5

Lisson : EN 1963 : < 30g/m²

Dimensional stability : EN 986 : meets the requirements for loose lay

Doming and curling: EN 986 : meets the requirements

Squareness and straightness of edges: EN 994 : meets the requirements

Castor chair suitability : EN 985 : intensive use

Walking test : ISO 6356 : < 2 kV - permanently antistatic



Acoustical insulation from impact noise Δ Lw : 14 dB

Drum Sound Absorption EPLF 021029-2 : 40 %

Light fastness : ISO 105-B02 : ≥ 7

Slip resistance : EN 13893 : > 0,3

Resistance to fire : EN 13501-1 : **B_{fl}s1**



EN 14.041
DOP Nr.
0493-CPR-0110

